


Aluminium Electrolytic Capacitor

Material Data Sheet

Product Class	Capacitors for pulse application with solder lugs	
Date	2016.01.25	
IMDS ID if available		
Version	08	

Remark: This material datasheet is valid for the part numbers contained in the Data Book 2015. In case of special (B4****S****) or obsolete capacitors please contact our sales department

Product Part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance	TMPS**) [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Light Metals	1B	Aluminium	100	7429-90-5	44	
	Acids, Bases, Salts	6F	Ethylene glycol	80	107-21-1	25	
	Acids, Bases, Salts	6F	Others*)	20	-		
	Thermoplastics	2A	Polypropylene	100	9003-07-0	0,1	
	Paper, Cardboard	5C	Cellulose	100	9004-34-6	11,9	
Encapsulation	Light Metals	1B	Aluminium	100	7429-90-5	11	
	Paper, Cardboard	5C	Cellulose	56	9004-34-6	2,7	
	Duromer	2D	Phenolic plastic	44	-		
	Elastomer	2B	EPDM rubber	41,5	25038-36-2		
	Inorganic, solid	4A	Silicon dioxide	13	7631-86-9	1,3	
	Inorganic, solid	4A	Kaolinite	28,5	1318-74-7		
	Lubricant	6B	Paraffin	10,5	8012-95-1		
	-	-	Others *)	6,5	-		
	Thermoplastics	2A	Polyvinyl chloride or Polyethylene terephthalate or without insulation	90	9002-86-2 25038-59-9	3,0	
		others*)	10	-			
Termination	Heavy Metal	1C	CuZn37	100	-	1	
	Heavy Metals	1C	Copper	100	7440-50-8	<0,1	
	Heavy Metals	1C	Tin	100	7440-31-5	<0,1	
Sum in total:						100	

sizes D x L [mm]	weight range [g]	sizes D x L [mm]	weight range [g]	sizes D x L [mm]	weight range [g]	sizes D x L [mm]	weight range [g]	part numbers
35-35,8 x 50	70	35-35,8 x 105	130	40-40,8 x 80	150	45 x 105	260	B43405 / B43406 / B43415
35-35,8 x 55	75	35-35,8 x 110	145	40-40,8 x 85	155	50-50,8 x 75	180	
35-35,8 x 65-65,8	88	40-40,8 x 40	75	40-40,8 x 90	160	50-50,8 x 80	230	
35-35,8 x 70	95	40-40,8 x 55	100	40-40,8 x 105	180	50-50,8 x 85	240	
35-35,8 x 80	105	40-40,8 x 65-65,8	115	40-40,8 x 110	190	50-50,8 x 100-100,8	270	
35-35,8 x 85	115	40-40,8 x 70	130	45 x 60	136	50-50,8 x 115,8	340	
35-35,8 x 90	125	40-40,8 x 75	140	45 x 85	190			

Not Part of a Product Class		Important remarks: 1) The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906). Traces are product parts, substances etc. that are below a percentage of 0.1 % by weight, if not otherwise regulated. 2) This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained herein are based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. EPCOS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.
Contact	Dr. Ildikó Szaraz	
Division	SZ CAP QA	
Address	Szent László u. 6. H-9700 Szombathely / Hungary	
	Tel: +36 94 522 319	mailto: ildiko.szaraz@epcos.com
*) others: (not declarable or prohibited substances acc. GADSL)		
**) typical mass percentage of substance		

The products set forth herein are "RoHS-compatible". RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

RoHS - Exemptions for the Product Class / Product according to Annex III: (valid not valid)

no exemptions;

- Exemption 6 (a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;
- Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;
- Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;
- Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);
- Exemption 7 (c)-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound;
- Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;
- Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC;
- Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;
- Other Exemption than above