

SMT Inductors

Product Class:		SIMID 1210-100 B82422A3****10*		103J 1394					
Date 18.10.2011									
IMDS ID									
if available									
Version: 06									
Product Part (IMDS: semi component)	Material (IMDS: N		Material (Classification) VDA 231	Substance		TMPS**) [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Ceramic		4B	Al ₂ O ₃		100	1344-28-1	33.3	
	Heavy Metal		1C	Cu		100	7440-50-8	9.7	
	Elastomer		2B	Polyurethane (PUR)		100	68400-67-9	0.4	
Encapsulation and Mounting	Thermoplastic		0.4	Polyphenylene sulfide (PPS) Glass fiber		60	26125-40-6	40.4	
			2A			40	65997-17-3	43.4	
	Duromer		2C	Epoxy (EP)		100	25068-38-6	1.3	
Termination	Heavy Metal		1C	Cu		94	7440-50-8	10.0	
			1C	Sn		6	7440-31-5	10.6	
	Heavy Metal		1C	Cu		100	7440-50-8	0.2	
	Heavy Metal		1C	Ag		100	7440-22-4	0.2	
	Heavy Metal		1C	Sn		100	7440-31-5	0.9	
Not part of a Pro		ss Reindl, MAG EP	OM		Important remarks:				
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	tics Business Grou						races are
		ner Strasse 116b.		(a) The declaration minimum of the declaration of the decl				
į	el: +49 89 54		mailto:						
			johann.reindl@tdk-ele	tronics.tdk.com herein. We expressly point out that all values and statements contained herein are					erein are
**) typical mass p	percentag	e of substance	tances acc. GADS		or binding product specifications, unless otherwise explicitly agreed in writing. TDK ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE. that products are compatible with the requirements according to Art. 4 (substance restrictions)				
					that products are compatible with the restriction of the use of certa				
RoHS - Exemp	otions fo	r the product c	lass / product ac	cording to Ann	ex III: (☑ valid □ not valid)				
 ☑ no exemptions; □ Exemption 6 (a): □ Exemption 6 (b): □ Exemption 6 (c): □ Exemption 7 (a): 	Lead as an Copper alloy	alloying element in alur containing up to 4 % I	ninium containing up to 0 ead by weight;	,4 % lead by weight;	containing up to 0,35 % lead by weigh	t;			
	Electrical an	d electronic componen ectric ceramic in capaci	ts containing lead in a gla tors for a rated voltage of	ass or ceramic other than 125 V AC or 250 V DC		piezoelectronic c	levices, or in a glass or	ceramic matrix con	npound;
Exemption 15:	Lead in sold				90 V DC; e and carrier within integrated circuit F	lip Chip package	95;		