

Inductor

Material Data Sheet

Product Class:	ERU25 SMD B82559A****A025	8 882559 8 432.045					
Date	30.03.2015	O 4435Wi					
IMDS ID							
if available							
Version:	05						

Product Part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance			TMPS**) [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Ceramic	4B	Manganese Zinc Ferrite		100	1264549-7	61.1		
	Heavy Metal	1C	Cu			100	7440-50-8	30.8	
	Elastomer	2B	Polyurethane (PUR)		100	9009-54-5	1.6	
Encapsulation	Duromer 2C		Epoxy resin (EP)			100	25068-38-6	3.4	
and Mounting	Duromer	Polyimide (PI)			100	26298-81-7	0.5		
	Elastomer	Acrylic polymer			100	9017-68-9	0.2		
Termination	Heavy Metal	1C	Cu			100	7440-50-8	2.2	
	Heavy Metal	1C	Sn			100	7440-31-5	0.2	
							Sum in total:	100.0	
Size W x L x H Weight [approx. in g] Part Numbers 25.3X23.5X8.95 22.1 B82559A1042A025 25.3X23.5X10.75 24.4 B82559A2122A025 25.3X23.5X10.75 21.8 B82559A3292A025 25.3X23.5X10.75 25.2 B82559A4432A025 25.3X23.5X12.7 26.5 B82559A3202A025 Not part of a product class					Size W x L x k [max. in mm] 25.3X23.5X11.95 25.3X23.5X11.95 25.3X23.5X12.85 25.3X23.5X12.85 25.3X23.5X17.50	[appro 29 26 27 29	x. in g] .5 .3 .5	Part Number B82559A3232A B82559A5612A B82559A6792A B82559A7103A B82559A0183A	025 025 025 025
	<u> </u>	2 EDOM		l Ima	a uta ut va usa ulca .				
	Dr. Johann Reindl, MAG EPQM			'	Important remarks:				
Address	TDK Electronics AG, Magnetics Business Group (MAG) Rosenheimer Strasse 116b, 81669 Munich				The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906) Traces a product parts, substances etc. that are below a percentage of 0.1 % by weight, if otherwise regulated				eight, if not
	Tel: +49 89 54020 3030	mailto:	ronics tdk com	2)	 This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained berein are 				

Contact	Dr. Johann Reindl, MAG EPQM				
Division	TDK Electronics AG, Magnetics Business Group (MAG)				
Address	Rosenheimer Strasse 116b, 81669 Munich				
	Tel: +49 89 54020 3030	mailto:			
		johann.reindl@tdk-electronics.tdk.com			

^{*)} others: .(not declarable or prohibited substances acc. GADSL)

herein. We expressly point out that all values and statements contained herein are based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. TDK ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE

The products set forth herein are "RoHS-compatible". RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

RoHS - Exemptions for the Product Class / Product according to Annex III: (☑ valid □ not valid)

☑ no exemptions;

□ Exemption 6 (a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;

☐ Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;

☐ Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;

□ Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);

□ Exemption 7 (c)-1: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound;

☐ Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;

☐ Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC;

☐ Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;

☐ Other Exemption than above ..

^{**)} typical mass percentage of substance