

## Inductor

Date IMDS ID if available Version: Product Part (IMDS: semi component) Active Part Encapsulation and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8 17x13.3x10.8	14.09.2015       05       Material Class (IMDS: Material)       Ceramic       Heavy Metal       Elastomer       Thermoplastic       Elastomer       Heavy Metal       Heavy Metal	Material (Classification) VDA 231 4B 1C 2B 2A 2A 2B 2A 2B 1C		(PUR)	rrite	TMPS**) [wt%] 100	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
if available         Version:         Product Part (IMDS: semi component)         Active Part         Encapsulation and Mounting         Termination         Size W x L x H [max. in mm] 17x13.3x10.8	Material Class (IMDS: Material)         Ceramic         Heavy Metal         Elastomer         Thermoplastic         Elastomer         Heavy Metal	(Classification) VDA 231 4B 1C 2B 2A 2A 2B	Manganese Zir Cu Polyurethane ( Liquid Crystal	(PUR)	rrite	[wt%]	if applicable	mass of material	
Version: Product Part (IMDS: semi component) Active Part Encapsulation and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Material Class (IMDS: Material)         Ceramic         Heavy Metal         Elastomer         Thermoplastic         Elastomer         Heavy Metal	(Classification) VDA 231 4B 1C 2B 2A 2A 2B	Manganese Zir Cu Polyurethane ( Liquid Crystal	(PUR)	rrite	[wt%]	if applicable	mass of material	
Product Part (IMDS: semi component) Active Part Encapsulation and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Material Class (IMDS: Material)         Ceramic         Heavy Metal         Elastomer         Thermoplastic         Elastomer         Heavy Metal	(Classification) VDA 231 4B 1C 2B 2A 2A 2B	Manganese Zir Cu Polyurethane ( Liquid Crystal	(PUR)	rrite	[wt%]	if applicable	mass of material	
(IMDS: semi component) Active Part Encapsulation and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	(IMDS: Material) Ceramic Heavy Metal Elastomer Thermoplastic Elastomer Heavy Metal Heavy Metal	(Classification) VDA 231 4B 1C 2B 2A 2A 2B	Manganese Zir Cu Polyurethane ( Liquid Crystal	(PUR)	rrite	[wt%]	if applicable	mass of material	
Encapsulation and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Heavy Metal Elastomer Thermoplastic Elastomer Heavy Metal Heavy Metal	1C 2B 2A 2B	Cu Polyurethane ( Liquid Crystal	(PUR)	rrite	100			
and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Elastomer Thermoplastic Elastomer Heavy Metal Heavy Metal	2B 2A 2B	Cu Polyurethane ( Liquid Crystal	(PUR)			12645-49-7	41.3	
and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Elastomer Thermoplastic Elastomer Heavy Metal Heavy Metal	2B 2A 2B	Liquid Crystal	,	- ·		7440-50-8	19.1	
and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Elastomer Heavy Metal Heavy Metal	2B	Liquid Crystal	,	Polyurethane (PUR)		9009-54-5	1.0	
and Mounting Termination Size W x L x H [max. in mm] 17x13.3x10.8	Elastomer Heavy Metal Heavy Metal	2B		Liquid Crystal Polymer (LCP)		70	90967-43-4		+
Termination Size W x L x H [max. in mm] 17x13.3x10.8	Heavy Metal Heavy Metal			,		30	65997-17-3	32.0	
Size W x L x H [max. in mm] 17x13.3x10.8	Heavy Metal Heavy Metal		Silicone (SI)		100	63148-62-9	1.3	+	
Size W x L x H [max. in mm] 17x13.3x10.8	Heavy Metal	10	Sn			100	7440-31-5	1.0	
Size W x L x H [max. in mm] 17x13.3x10.8	-		Cu			94	7440-50-8	-8 4.1	
[max. in mm] 17x13.3x10.8	Heavy Metal	1C				-			
[max. in mm] 17x13.3x10.8	Heavy Metal		Sn			6	7440-31-5		
[max. in mm] 17x13.3x10.8	-	10	Ni			100	7439-89-6		Х
[max. in mm] 17x13.3x10.8	Heavy Metal	1C	Sn			100	7440-31-5	0.2	
[max. in mm] 17x13.3x10.8							Sum in total:	100.0	
[max. in mm]       [approx. in g]         17x13.3x10.8       2.5       B82         17x13.3x10.8       2.3       B82		Part Numbers B82720S2301N042 B82720S2152N040 B82720S2301N240 B82720S2102N040 B82720S2152N240 B82720S2551T040	2720S2301N042 2720S2152N040 2720S2301N240 2720S2102N040 2720S2152N240		Size W x L x H [max. in mm] 17x13.3x10.8 17x13.3x10.8 17x13.3x10.8 17x13.3x10.8 17x13.3x10.8	Weight [approx. in g] 2.5 2.5 2.5 2.5 2.5 2.5		Part Numbers B82720S2202N040 B82720S2301N040 B82720S2301N041 B82720S2601N040 B82720S2301N240	
Not part of a Produc	ct Class								
Contact Dr. Jo	Johann Reindl, MAG EF	PQM		lm	portant remarks:				
Division TDK I	Electronics AG, Magne	etics Business Group (N	1)	The declaration limit is 0					
Address Rose	enheimer Strasse 116b, 81669 Munich			product parts, substanc otherwise regulated		es etc. that are	e below a percentag	e of 0.1 % by we	ight, if not
Tel: +4	+49 89 54020 3030	mailto:			This Material Data Shee	et contains typical values of the respective products set forth			
*) others: .(not declara **) typical mass perce	rable or prohibited subs centage of substance	johann.reindl@tdk-e tances acc. GADSL)	lectronics.tdk.com		herein. We expressly po based on our best presse or binding product speci ELECTRONICS AG AN REPRESENTATION OF STATUTORY, WITH RE HEREIN, INCLUDING B WARRANTY OF MERC	nt knowledge fications, unle D ITS AFFILIA WARRANT GARD TO TH UT NOT LIMI	and cannot be rega ss otherwise explici ATES HEREBY EXP (, WHETHER EXPR HE STATEMENTS A TED TO ANY REPF	arded as binding tly agreed in writ PRESSLY DISCL ESS, IMPLIED ( ND VALUES CO RESENTATION (	statements ing. TDK AIM ANY DR DNTAINED DR
Directive 2011/65/EU of t ROHS - Exemptions Directive 2011/65/EU of t ROHS - Exemptions Exemption 6 (a): Lead Exemption 6 (b): Lead Exemption 6 (c): Copper	f the European Parliament s for the Product Class d as an alloying element in stee d as an alloying element in alun per alloy containing up to 4 % le	and of the Council of June <b>c / Product according</b> I for machining purposes and ir ininium containing up to 0,4 % le ead by weight;	8 <sup>th</sup> , 2011 on the rest to Annex III: ( 교 n galvanized steel contai ead by weight;	striction valid ⊏ aining up	to 0,35 % lead by weight;				
Exemption 7 (c)-I: Electr Exemption 7 (c)-II: Lead Exemption 7 (c)-III: Lead	d in high melting temperature ty ctrical and electronic componen d in dielectric ceramic in capaci d in dielectric ceramic in capaci d in solders to complete a viable	ts containing lead in a glass or tors for a rated voltage of 125 \ tors for a rated voltage of less t	ceramic other than diele / AC or 250 V DC or high han 125 V AC or 250 V I	ectric cer gher; DC;	ramic in capacitors, e.g. piezoelec		or in a glass or ceramic	matrix compound;	

C TDK Electronics AG 2019 • Page 1/1