

Chokes for Power Lines

Product Class:	Ring Core Double Choke		
	B82726Sx223X***		
Date	26.07.2021		
IMDS ID if available			
Version:	03	83 89	

Product Part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance	TMPS**) [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)
Active Part	Ceramic	4B	Manganese-zinc ferrite	100	12645-49-7	46.3	
	Polymer	2C	Epoxy (EP)	100	25068-38-6	1.0	
	Metal	1C	Cu	100	7440-50-8	44.8	
	Delumer	2C	Polyester-imide (THEIC) 50 839-90-7		839-90-7	0.9	
	Polymer	20	Polyamide-imide (PAI)	AI) 50 31957–38–7		0.5	
Encapsulation and Mounting	Thermoplastic	2A	Polycarbonate (PC)	89.8	25971-63-5		
			Glass fiber	10	65997-17-3	5.5	
			PFBS	0.2	29420-49-3		
	Polymer	2A	Polyethyleneterephthalate (PET)	100	25038-59-9	1.3	
	Polymer	2A	Polyacrylate	100	37325-11-4		Х
Termination	Metal	1C	Sn	100 7440-31-5		0.1	
Label	Polymer	2C	Polyethylentherephthalate PET	100	25038-59-9	0.1	
	Polymer	2C	Acrylic resin	100	37325-11-4		Х
					Sum in total:	100.0	

Size W x L x H	Weight	Part N
[max. in mm]	[approx. in g]	
55 x 50 x 34	150	B82726S
55 x 34 x 55	153	B82726S

Fait Nullibers
B82726S6223N040

B82726S3223A340

Contact	Dr. Johann Reindl, MAG EPQM		Important remarks:		
Division			1)	The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906) Traces are	
Address				product parts, substances etc. that are below a percentage of 0.1 % by weight, if not otherwise regulated.	
	Tel: +49 89 54020 3030	mailto:	2)	This Material Data Sheet contains typical values of the respective products set forth	
		johann.reindl@tdk-electronics.tdk.com		herein. We expressly point out that all values and statements contained herein are	
*) others: not declarable or prohibited substances acc. GADSL			based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. TDK		
**) typical mass percentage of substance			ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY		
				REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR	
				STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED	
				HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR	
				WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.	

The products set forth herein are "RoHS-compatible". RoHS-compatible means that products are compatible with the requirements according to Art. 4 (substance restrictions) of Directive 2011/65/EU of the European Parliament and of the Council of June 8th, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment.

RoHS - Exemptions for the Product Class / Product according to Annex III: (🗹 valid 🗆 not valid)

☑ no exemptions;

Exemption 6 (a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;

Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;

Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;

Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);

Exemption 7 (c)-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound;

- Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;
- Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC;

Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;

Other Exemption than above ...