

Chokes for Power Lines

Date

Version:

Product Part

(IMDS: semi

component)

Active Part

Encapsulation and

Mounting

Termination

Size W x L x H

[max. in mm]

16,5 x 24 x 23

Material Data Sheet Product Class: **D** Core Double Choke B82732R2xxxBxxx Vertical version 26.07.2021 IMDS ID if available 04 TMPS**) [wt%] Material Class Material Substance CAS typical mass Traces (Classification) VDA 231 if applicable (IMDS: Material) of material see 1) [wt-%] 4B Manganese Zinc Ferrite 100 12645-49-7 44 Ceramic 1C 100 38 Heavy Metal 7440-50-8 Cu Duromer 2C Polyurethane (PUR) 100 2 68400-67-9 Polycarbonate (PC) 89.8 25971-63-5 Thermoplastic 2A 65997-17-3 14 Glass fiber 10 PFBS 0.2 29420-49-3 Heavy Metal 100 7440-31-5 0.5 1C Sn 1C Cu 7440-50-8 62 Heavy Metal 1C Ni 18 7440-02-0 1.4 1C Zn 20 7440-66-6 Ni Heavy Metal 1C 100 7440-02-0 х Heavy Metal Sn 100 7440-31-5 0.1 1C Sum in total: 100.0 Weight Part Numbers [approx. in g] B82732R2***B*** 11 Not part of a Product Class

Contact	Dr. Johann Reindl, MAG EPQM		Important remarks:	
Division	TDK Electronics AG, Magnetics Business Group (MAG)		1)	 The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906) Traces are product parts, substances etc. that are below a percentage of 0.1% by weight, if not otherwise regulated.
Address	Rosenheimer Strasse 116b, 81669 Munich			
	Tel: +49 89 54020 3030	mailto: johann.reindl@tdk-electronics.tdk.com	2)	 This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained herein are
*) others: .(not declarable or prohibited substances acc. GADSL)				based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. TDK
**) typical mass percentage of substance				ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.
				roducts are compatible with the requirements according to Art. 4 (substance restrictions) of riction of the use of certain hazardous substances in electrical and electronic equipment.
RoHS - Exe	emptions for the Product C	lass / Product according to Annex III:	(⊠v	valid □ not valid)
☑ no exempti	ons;			
Exemption 6	(a): Lead as an alloying element in steel for machining purposes and in galvanized steel containing up to 0,35 % lead by weight;			
Exemption 6 (b): Lead as an alloying element in aluminium containing up to 0,4 % lead by weight;				
Exemption 6 (c): Copper alloy containing up to 4 % lead by weight;				
Exemption 7 (a): Lead in high melting temperature type solder (i.e. lead-based alloys containing 85 % by weight or more lead);				
🗖 Eventies 7 (s) k. Electrical and electronic concerned contricing land in a glass or commit attraction that they dialectric control is a second device of a size of a second device of				

Exemption 7 (c)-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound;

Exemption 7 (c)-II: Lead in dielectric ceramic in capacitors for a rated voltage of 125 V AC or 250 V DC or higher;

Exemption 7 (c)-III: Lead in dielectric ceramic in capacitors for a rated voltage of less than 125 V AC or 250 V DC:

Exemption 15: Lead in solders to complete a viable electrical connection between semiconductor die and carrier within integrated circuit Flip Chip packages;

Other Exemption than above