

Surge Arrester

Material Data Sheet

Product Class	A80-A*XSMD, A80-C*XSMD B88069X*(Tin plated) 11/28/2023							
Date								
IMDS ID if available								
Version	5.01							
Product Part (IMDS: semi component)	Material Class (IMDS: Material)	Material (Classification) VDA 231	Substance	TMPS**) [wt%]	CAS if applicable	typical mass of material [wt-%]	Traces see 1)	
Active part	Ceramic	3B	Al203	100	1344-28-1	24		
	Metal	1C11	Cu	100	7440-50-8	72		
Brazing ring	Metal	4D	Ag	72	7440-22-4	3		
			Cu	28	7440-50-8			
Plating	Metal	1C8	Sn	100	7440-31-5	1		
sizes [mm]	weight range[g] part name				Sum of total material numbers	100		
Ø6 X 6	1.5	A80-A75XSMD A80-A90KSMD A80-A230XSMD A80-A500XSMD A80-C90XSMD A80-C90XSMDHC A80-C90ZSMD	90KSMD 230XSMD 500XSMD 90XSMD 90XSMDHC		B88069X6350* B88069X4683* B88069X1620* B88069X8103* B88069X1630* B88069X4223* B88069X5943*	B88069X1620* B88069X8103* B88069X1630* B88069X4223*		
Not part of a Product (Class							
Contact	Mohd Faizal Jamaludi	n		Important remar	ks:			
Division	TDK ELECTRONICS (MALAYSIA) SDN BHD			1) The deale	The dedecation limit is 0.40/ as defined by UEO COAZA (UEO DAO CARRO). T			
Address	11 Jalan Firma 3 Tebr	au Ind IV, 81100 JB Mal	aysia	 The declaration limit is 0.1% as defined by IEC 62474 (IEC PAS 61906). Traces are product parts, substances etc. that are below a percentage of 0.1 % by weight, if not otherwise 			,	
	Tel: +60-7-3566629	Tel: +60-7-3566629 mailto: mohdfaizal.jamaludin@tdk.com			regulated.			
*) others: .(not declarable or prohibited substances acc. GADSL) **) typical mass percentage of substance				2) This Material Data Sheet contains typical values of the respective products set forth herein. We expressly point out that all values and statements contained herein are based on our best present knowledge and cannot be regarded as binding statements or binding product specifications, unless otherwise explicitly agreed in writing. TDK ELECTRONICS AG AND ITS AFFILIATES HEREBY EXPRESSLY DISCLAIM ANY REPRESENTATION OR WARRANTY, WHETHER EXPRESS, IMPLIED OR STATUTORY, WITH REGARD TO THE STATEMENTS AND VALUES CONTAINED HEREIN, INCLUDING BUT NOT LIMITED TO ANY REPRESENTATION OR WARRANTY OF MERCHANTABILITY OR SUITABILITY FOR ANY PURPOSE.				
the European Parliamer	nt and of the Council of	June 8 th , 2011 on the re	striction of the use of cert	ain hazardous substances in	uirements according to Art. 4 (s electrical and electronic equipm	,	irective 2011/65/EU of	
	ead as an alloying element ead as an alloying element opper alloy containing up to ead in high melting temper icletrical and electronic core ead in dielectric ceramic in ead in solders to complete	t in steel for machining purp t in aluminium containing up o 4 % lead by weight; ature type solder (i.e. lead- nponents containing lead in capacitors for a rated volta capacitors for a rated volta a viable electrical connecti	to 0,4 % lead by weight; based alloys containing 85 % a glass or ceramic other that ge of 125 V AC or 250 V DC ge of less than 125 V AC or	containing up to 0,35 % lead by by weight or more lead); n dielectric ceramic in capacitors, or higher;	, e.g. piezoelectronic devices, or in	a glass or ceramic matrix com	pound;	